

# **INSTALLATION MANUAL**

## **100SW**

### **LOW ENERGY OPERATOR**




## TABLE OF CONTENTS

---

PRODUCT SPECIFICATIONS	3
COMPONENTS	4
INSTALLATION	
A. INSTALLATION EXAMPLE	5
B. PULL ARM INSTALLATION	6-9
C. PUSH ARM INSTALLATION	10-14
ELECTRICAL CONNECTION	15-19
PARAMETERS ADJUSTMENT	20


## PRODUCT SPECIFICATIONS

<b>Mounting:</b>	Surface applied, single leaf.
<b>Minimum frame face:</b>	1-3/4"
<b>Minimum clearance from Top of door to ceiling:</b>	7"
<b>Standard finish:</b>	Clear anodized.
<b>Optional finishes:</b>	Powder coating, any color.
<b>Basic Features:</b>	Obstacle detection during cycle.
	Adjustable opening and closing speed.
	Adjustable hold open time.
	Adjustable opening angle.
<b>Optional:</b>	Low energy operation
	Remote control.
	Backup battery.
	Two door synchronization function.
	Two door interlock function.
	Auxiliary sensing device.
<b>Limited door weight:</b>	225lbs.
<b>Limited door width:</b>	48".
<b>Power voltage:</b>	110 VAC, 1-phase to 24VDC
<b>Dimensions:</b>	21" L x 4-1/4" H x 3-1/4" W
<b>Supply Voltage:</b>	100-240V
<b>Power Consumption:</b>	50W
<b>Opening Time:</b>	1-30s
<b>Hold Open Time:</b>	1-3
<b>Max. Door Frame Depth:</b>	18"
<b>Max. Opening Angle:</b>	120°
<b>Environment Temperature:</b>	-20°C - 50°C
<b>Protection Class:</b>	IP12D
<b>Product Weight:</b>	14.33 lbs



## COMPONENTS

### OPERATOR



### COVER



### BASEPLATE



### PUSH ARM



### PULL ARM




## INSTALLATION

### 1.1 Installation Example


#### Pull Arm:

Pulls the door towards the person. Operator is placed on the inside.




#### Push Arm:

Pushes the door away from the person. Operator is placed on the outside.




## PULL ARM INSTALLATION

### 2.1 Installation of Baseplate for Pull Arm




## PULL ARM INSTALLATION

### 2.1 Installation of Baseplate for Pull Arm




### 2.2 Adjusting Angle on Stopper for Pull Arm




## PULL ARM INSTALLATION

### 2.3 Installing Operating System for Pull Arm



Hook the operating system on the finished base plate as shown, fix it with eight hexagon socket head screws

### 2.4 Installing Cover for Pull Arm





Opening the cover




## PULL ARM INSTALLATION

### 2.5 Connecting the Operation System and the Pull Arm





## PUSH ARM INSTALLATION

### 3.1 Installation of Baseplate for Push Arm



## PUSH ARM INSTALLATION

### 3.1 Installation of Baseplate for Push Arm




Loosen these **three** bolts and adjust the push arm length according to the door depth(L) until the angle between the push arm and the door panel is 90°.

At door right


## PUSH ARM INSTALLATION

### 3.2 Adjusting Angle on Stopper for Push Arm




## PUSH ARM INSTALLATION

### 3.3 Installing Operating System for Push Arm



Hook the operating system on the finished base plate as shown,  
fix it with eight hexagon socket head screws


### 3.4 Installing Cover for Push Arm




Opening the cover

## **PUSH ARM INSTALLATION**


### 3.5 Connecting the Operation system and the Push Arm




## ELECTRICAL CONNECTION




### Safety Sensor



### Sensor and Access Control




## ELECTRICAL CONNECTION




### Electric Lock (Automatic Lock)

The door will be locked everytime while it is fully closed




### Electric Lock (Remote Control Lock)

When the door is fully closed, press “lock” button on remote control for locking




### Backup Battery






## ELECTRICAL CONNECTION

### Double-Door Synchronous




### Inter-lock



Note: Two doors share same sensor or same signal source, both doors may hold open, in this case, exchange two signal wires of the sensor which is connected with the same controller, it doesn't matter controller A or B.

## ELECTRICAL CONNECTION


Optional: Functional Key Switch



1. When the key switch is set “Oneway”, the sensor signal is shielded but the access control works normally.
2. When the key switch is set “Lock”, both the sensor signal and access control are shielded.

## ELECTRICAL CONNECTION

### Optional: Remote Control



Encode remote control with the door controller:

1. Delete all: long press the button “Encode” until the sound of buzzer disappears, loosen the button.
2. Encoding: Press the button “Encode”, the buzzer sounds. Then press any button of the remote control, the buzzer stops sounding which means encoding successfully. When use the remote control, the buzzer sounds for 2 seconds.
3. Note: When use the remote control, if the buzzer “deep” twice, it means encoding failed, so please repeat above step 2.
4. Press button “Automatic” one time, the door will open and close one time.


A: Lock: The sensor signal is shielded, but the access control works normally;

B: Hold-open: The door will open and hold-open until press button C to release;

C: Reset: Cancel A,B,D setting;

D: Auto: Both the sensor signal and access control are effective

## PARAMETERS ADJUSTMENT



1. Set the DIP switch (K1-K4): after setting, power off and restart.

K1: Set opening direction: power on, the door goes to closing direction, if not, turn K1 up (ON) (turn to opposite);

K2: Set master/slave door: when double-door synchronous, master door turn K2 down (OFF), slave door turn K2 up (ON);

K3: Set closed force: no closed force, turn K3 down (OFF), want closed force, turn K3 up (ON);

K4: Choose pull arm or push arm: pull arm, turn K4 down (OFF), push arm, turn K4 up (ON).

2. User Adjustment:

- |                       |                                |
|-----------------------|--------------------------------|
| 1. Opening speed      | turn clockwise, speed increase |
| 2. Slow opening angle | turn clockwise, angle bigger   |
| 3. Closing speed      | turn clockwise, speed increase |
| 4. Slow closing angle | turn clockwise, angle bigger   |
| 5. Hold-open time     | turn clockwise, time longer    |

Turn anticlockwise, means decrease.